Select the USB line
Select the RS232 line
Once you have selected the line, just connect the cable.
If the line selected is RS232: RS232 PC cable (see chapter 7). The communication can be extremely slow and one could not be able to use some systems).
If the line selected is USB: USB cable (see chapter 7).
If the connection is via LAN (recommended): cross-over cable (see chapter 7).

No cable needed in case of wireless connection.

- Press "Language" to modify the language used in the SD3NET screens.(fig 2.4.1).
Press the button just below the language flag to confirm your choice and automatically exit the window. To void without saving, press "Esc" or press the cancel key.
The language selected on the SD3 only affects the messages for the routine software which selects and runs the diagnostics programs (basic SD3NET software). The diagnostics software language, on the other hand, is selected in the PC initialization software; to avoid any possible inconsistencies, make certain that the PC and SD3 are both using the same language.
Press "Esc" to return to the previous menu.

WARNING. TO SAVE TESTER DISK SPACE, THE DIAGNOSTICS SOFTWARE IS ONLY DOWNLOADED IN ONE LANGUAGE (DEPENDING ON THE BASIC SD3NET SOFTWARE SETTINGS ON THE PC).
TO SET THIS SOFTWARE TO ANOTHER LANGUAGE, YOU MUST SELECT THE DESIRED LANGUAGE ON THE PC AND THEN UPDATE THE TESTER LANGUAGE.

Fig. 2.4.3